

RX Series HD Rotary Tillers

Standard features include:

- Tillers are available with either chain drive or gear drive
- Spiral gears for the top gearbox
- 6 Blades per flange
- Series 60 PTO drive shaft with Slip Clutch-Option
- Heavy Duty zinc plated Jack Stand
- Powder coating finishing



2207 Vista Chaparral
 Carlsbad, CA 92009, USA
 Tel: 001 760 6210018
 Fax: 001 760 4544549
 bill.yuan@autotechgear.com



Side Chain Drive or Gear Drive





Spiral Gears for the top gearbox



Individule packing



Metal Gearbox Shield

Model	Tilling Width (MM)	Working Depth	No. Of Tines	No. of Rotor Flanges	Weight w/PTO (LBS)	Horse Power Required	Side Drive	PTO Shaft	PTO Protection	
RX160G		9 3/4"	48		847	60-90 HP		#60-900E	200mm Slip Clutch	
RX180G		9 3/4"	54		902	60-90 HP		#60-900E	200mm Slip Clutch	
RX200G	1960	9 3/4"	60		957	60-90 HP		#60-900E	200mm Slip Clutch	
RX220G	2150	9 3/4"	66		1012	60-90 HP		#60-900E	200mm Slip Clutch	
RX240G	2340	9 3/4"	72		1067	60-90 HP		#60-900E	200mm Slip Clutch	
RX160C		9 3/4"	48		792	60-90 HP		#60-900E	200mm Slip Clutch	
RX180C		9 3/4"	54		847	60-90 HP		#60-900E	200mm Slip Clutch	
RX200C	1960	9 3/4"	60		902	60-90 HP		#60-900E	200mm Slip Clutch	
RX220C	2150	9 3/4"	66		957	60-90 HP		#60-900E	200mm Slip Clutch	
RX240C	2340	9 3/4"	72		1012	60-90 HP		#60-900E	200mm Slip Clutch	