

TS Series Rotary Tillers

Standard features include:

- Tillers are available with either chain drive or gear drive
- 6 Blades per flange
- Series 50 PTO drive shaft with Slip Clutch
- Single piece structure Top Hitch and Double Torque Tube
- Heavy Duty zinc plated Jack Stand
- Lower Links adjustable
- Reverse Till is available



2207 Vista Chaparral
 Carlsbad, CA 92009, USA
 Tel: 001 760 6210018
 Fax: 001 760 4544549
 bill.yuan@autotechgear.com



Side Gear Drive or Chain



Rotor with 6 blades per Flange




Packing



PTO Shield



PTO shaft with Slip Clutch

Model	Tilling Width	Working Depth	No. Of Tines	No. of Rotor Flanges	Weight w/PTO	Horse Power Required	Side Drive	PTO Drive
TS-58G 	58"	7 1/2"	42	7	646 Lbs.	20-50 HP	Gear Drive	#40 w/ Slip Clutch
TS-66G	66"	7 1/2"	48	8	685 Lbs.	30-50 HP	Gear Drive	#40 w/ Slip Clutch
TS-72G	72"	7 1/2"	54	9	740 Lbs.	30-50 HP	Gear Drive	#40 w/ Slip Clutch
TS-81G	81"	7 1/2"	60	10	973 Lbs.	35-60 HP	Gear Drive	#60 w/ Slip Clutch

