



## Super 75 Series

### APPLICATIONS

Rotary Cutters

### SPECIFICATIONS & FEATURES

Lubricant: EP-90  
 Casing: Ductile iron casting  
 Input shaft: 1 3/8"-6 or 1 3/4"-20 Splines  
 Output shaft: 2" Tapered 15 Tooth Spline with 1"-14UNS-2A Thread  
 Gears: Gleason Coniflex cut tooth; case hardened.  
 PTO input: 540 RPM and 1000 RPM  
 Approx. Weight: 121 Lbs, 55 Kgs

P/N	Rotation	Ratio	Input Shaft	Output Shaft
01-307	75S	1:1.46SU	1 3/4"-20 Spline	1 9/16" Tapered Spline
01-313	75S	1:3SU	1 3/4"-20 Spline	1 9/16" Tapered Spline
01-343	75S	1:1.93SU	1 3/8"-6B Spline	1 9/16" Tapered Spline
01-346	75S	1:1.46SU	1 3/8"-6B Spline	1 9/16" Tapered Spline
01-378	75R	1:1.46SU	1 3/4"-20 Spline	1 9/16" Tapered Spline
01-397	75S	1:1SU	1 3/8"-6B Spline	1 9/16" Tapered Spline
01-398	75S	1:1.21SU	1 3/8"-6B Spline	1 9/16" Tapered Spline
01-400	75R	1:1.21SU	1 3/8"-6B Spline	1 9/16" Tapered Spline
01-405	75S	1.21:1RD	1 3/4"-20 Spline	1 9/16" Tapered Spline
01-669	75R	1:1.21SU	1 3/4"-20 Spline	1 9/16" Tapered Spline
01-677	75S	1:1.21SU	1 3/4"-20 Spline	1 9/16" Tapered Spline

HORSE POWER RATING  
 540 PTO - 88  
 1000 PTO - 135

