

TL Series Rotary Tillers-Side Chain Drive

Standard features include:

- Side Drives are chain drives
- 4 Blades per Flange
- Shear Bolt or Slip Clutch PTO Shaft
- Guard bars to meet the CE requirement
- CE Certified.



2207 Vista Chaparral
 Carlsbad, CA 92009, USA
 Tel: 001 760 6210018
 Fax: 001 760 4544549
 bill.yuan@autotechgear.com



Treated wood crate packing

PTO shaft with Slip Clutch

Guard Bar

Model	Working Width (CM)	Number of Blades	Tilling depth (CM)	Horse Power (HP)	Net weight (KG)	Shipping weight (KG)	Chain Size	Hitch Cat	Container Q'ty	
									40' GP	40' HQ
TL85	85 (33.5")	16	8-12	18	120	152	12A (60H)	Cat. I	99	132
TL95	95(37.4")	16	8-12	20	128	160	12A (60H)	Cat. I	90	120
TL105	105 (41.5")	20	8-12	22	138	172	12A (60H)	Cat. I	84	112
TL115	115 (45.3")	24	8-12	22-25	148	182	16A (80H)	Cat. I	75	100
TL125	125 (49.2")	28	8-12	25-30	158	192	16A (80H)	Cat. I	72	96
TL135	135 (53.2")	28	8-12	30-35	168	202	16A (80H)	Cat. I	66	88